



FLAT RAIL

Rail for wall and ceiling cladding

REF	DESCRIPTION	QTY/PALETTE	CONSUMMATION INDICATIVE PER M ²
1185	FLAT RAIL - clip spacing 124 mm 32 clips for 16 boards of 120 mm 12 x 55 x 1984 mm.	216 pcs	0,85 pc
1187	FLAT RAIL - clip spacing 71 mm 28 clips for 28 boards 12 x 55 x 1988 mm.	216 pcs	0,85 pc
1188	FLAT RAIL - clip spacing 56 mm 35 clips for 35 boards 12 x 55 x 1960 mm.	216 pcs	0,85 pc
1792	FLAT RAIL - clip spacing 70 mm 28 clips for 28 boards 12 x 55 x 1960 mm.	216 pcs	0,85 pc
1799	FLAT RAIL - clip spacing 51 mm 39 clips for 39 boards 12 x 55 x 1989 mm.	216 pcs	0,85 pc
1822	FLAT RAIL - clip spacing 69 mm 29 clips for 29 boards 12 x 55 x 2001 mm.	216 pcs	0,85 pc
2480	FLAT RAIL - VARIBO 32 clips for 25 boards 12 x 55 x 1968 mm.	216 pcs	0,85 pc
2191	FLAT RAIL - clip spacing 46 mm 43 clips for 43 boards 12 x 55 x 1978 mm.	216 pcs	0,85 pc
2632	FLAT RAIL - clip spacings 58,5 mm 34 clips for 34 boards. 12 x 55 x 1989 mm.	216 pcs	0,85 pc

TECHNICAL CHARACTERISTICS

Rail material	Aluminum 6060
Rail finish	Black paint
Clip material	Polyoxymethylene (POM)
Rail weight (including clips)	+/- 0,630 kg/ml
Maximum length	3968 mm
Pull-out strength of the clip on the rail	150 to 250 kg, for two fixing points (depending on the type of board)

- **Non load-bearing rail** to be used for wall or ceiling cladding
- Thin
- Industrially pre-clipped rail for perfect drainage lines
- Each board can be removed individually with special keys adapted to the width of the board
- Rail can be cut to length
- No contact between the boards and the aluminum rail for better air circulation
- Invisible fastening
- Simple, quick and comfortable installation
- Infinite possibilities
- 100% recyclable