

## GRO BENCHES



### Product description

The GRO is a playful but timeless park bench. The bench can be produced with and without armrest. You can use it as a 1-seater, 2-seater and 3-seater bench.

In the same series we also have a **picnic combination and litter bins**. You can find these at our product categories.

## SPECIFICATIONS

### General

Our benches are always equipped with:

- Mounting holes for fixing to surface
- Warranty 5 years (expiring)

### Standard material

#### Frame material

- Corten steel 5 mm
- Galvanised steel 5 mm + 2 layer powder coating

#### Seat material

- Material: Garapa
- Head sizes: 60x40 mm

### Options

- Moso Bamboo Extreme Seat
- FURNS Concrete footing

## IMPORTANT

### Points of attention

- All products must be unpacked immediately after delivery.
- Every kind of (hard) wood will turn grey under the influence of UV radiation, weather and wind. The final colour depends on the starting colour.
- Wood is a natural product that "works" and will shrink or expand depending on temperature and moisture content.
- Hardwood can turn black when in contact with Corten steel, which will eventually turn grey.
- Corten Steel should never be constantly in moisture, it should drain well and ventilate in all situations.
- Corten Steel products are not (fully) rusted on delivery, we only use Corten steel type S355J0WP.
- Coastal areas: We do not recommend using Corten steel within a radius of 2 km from a coastline.
- During the weathering process rust residue can come off the product, which can result in stains.
- Drilling / grinding in the material is not permitted.

### Maintenance

- Regular cleaning (WOCA exterior cleaner) and sealing (WOCA exterior oil) of the wood ensures that the pigment in the wood is retained longer and the discolouration process is delayed.
- Annual cleaning by removing dirt using clean tap water.

**Note!** Do not use a high-pressure cleaner.

# PLACEMENT

## PLACEMENT

1. Provide a flat, solid (vibrated) surface. If not done carefully, it can create stresses in the product which could result in damage to the product.

2. Place the FURNS concrete footings in the desired position and set them for a stable base.

3. Place the GRO bench on the concrete bases so that the holes in the base plate match the screw sleeves of the base. Use a forklift if necessary for the weight of the bench.

**Pay attention!** To prevent damage to the product, we recommend fitting the forks of the forklift truck protective material.

**Pay attention!** When moving the bench, the bench must be supported at the ends. The bench should be set down carefully.

4. Place the bench on the concrete base so that the holes in the base plate match the screw sleeves of the base.

**Pay attention!** Loosely tighten all bolts first, after which they can be tightened one by one.

## Armrest

An existing bench with a backrest can easily be fitted with an armrest.

To do this, remove the 4th and 5th bars of the backrest from top to bottom. Slide the armrest at the back between the backrest frames and at the front between the front beam and the seat frame. Then place the two beams back and fasten the armrest to the existing frame and beams.

5. Cover the concrete base and base plate with soil and finish the pavement.

**Pay attention!** Make sure that the footplate is 150 mm below ground level to maintain a seat height of 450 mm.





# GRO BENCHES

## MODELS

For a complete overview of all our products and specifications, please visit [www.furns.com](http://www.furns.com).



GRO 500 WITH BACKREST



GRO 1500 WITH BACKREST



GRO 2300 WITH BACKREST



GRO ARMREST



GRO 2000 SENIORS



GRO 2600 SENIORS



GRO 2300



GRO 2300 TABLE



GRO 2300 COMBINATION

## OPTIONS




CUSTOM MADE

# ACCESSORIES

## ACCESSORIES

All our accessories meet the highest standards and are an highly suitable addition to our products. Visit [www.furns.com](http://www.furns.com) for a complete overview of our accessories.



### CONCRETE FOOTING

We advise to place our products on our uniform concrete bases. These are suitable for installation below ground level. As standard, they are fitted with screw sleeves for easy mounting of our products. See the table below for the corresponding bases per model.

Product	Model	Concrete footing	Quantity
GRO 500 WITH BACKREST	GRBE.500SB	600	2
GRO 1500 WITH BACKREST	GRBE.1500SB	600	2
GRO 2300 WITH BACKREST	GRBE.2300SB	600	2
GRO 2000 SENIORS	GRBE.2000SAS	600	4
GRO 2600 SENIORS	GRBE.2600SAS	600	5
GRO 2300	GRBE.2300S	600	2
GRO 2300 TABLE	GRTA.2300	250	4
GRO 2300 COMBINATION	GRPNC.2300	250 600	4 4



### CLEANER & PROTECTOR

We recommend cleaning our products at least once a year. For optimal results, use the ADEZZ BIO Cleaner & Protector detergent. Always read the instructions on the package carefully before use.



### CORTEN VARNISH

To stop the rusting process, Corten varnish can be applied on the Corten products. Always read the instructions on the package carefully before use.