



PR24

Load-bearing rail for decking.

PR24

REF	DESCRIPTION	QTY/PALETTE	COMPATIBILITY
1191	PR24 - 124 32 clips for 16 boards of 120 mm. 24 x 55 x 1984 mm.	108 pcs	Accoya®, Kebony®, Moso®, Thermofrêne, Thermpin
1997	PR24 - 124 64 clips for 32 boards of 120 mm. 24 x 55 x 3968 mm.	108 pcs	
2033	PR24 - 145 26 clips for 13 boards of 140 mm. 24 x 55 x 1885 mm.	108 pcs	UPM
1192	PR24 - 150 26 clips for 13 boards of 145 mm. 24 x 55 x 1950 mm.	108 pcs	Nekko
1970	PR24 - 155,5 24 clips for 12 boards of 150 mm. 24 x 55 x 1866 mm.	108 pcs	Dex
1782	PR24 WITHOUT CLIPS For tapered boards. 24 x 55 x 1984 mm.	108 pcs	

TECHNICAL CHARACTERISTICS

Rail material	Aluminum 6060
Rail finish	Black paint
Clip material	Polyoxymethylene (POM)
Rail weight (including clips)	+/- 1,05 kg/ml
Maximum length	3968 mm
Pull-out strength of the clip on the rail	150 to 250 kg, for two fixing points (depending on the type of board)

- Load-bearing rail, pedastal spacing up to 38 cm for private use.
- Industrially pre-clipped rail for perfect drainage lines
- Each board can be removed individually with special keys adapted to the width of the board
- Rail can be cut to length
- No contact between the boards and the aluminum rail for better air circulation
- Invisible fastening
- Simple, quick and comfortable installation
- Infinite possibilities
- 100% recyclable